

OPTICAL FIBER LIGHT-TRANSMISSIVE STRUCTURE

BACKGROUND OF THE INVENTION

5 (a) Field of the Invention

The invention relates to an optical fiber light-transmissive structure, and more particularly, to an optical fiber light-transmissive structure having a long and thin shape, wherein light beams inputted into an end thereof are transmitted in an almost total reflection manner to the other end
10 thereof with minimal attenuation. The optical fiber light-transmissive according to the invention is suitable for applications of decorative purposes such as optical fiber bouquets, light Christmas trees and wings of angel dolls.

(b) Description of the Prior Art

15 Large numbers of optical fiber cords are generally used in optical fiber applications of decorative purposes. One end (usually an input end) of the optical fiber cords is bundled, and cords of individual optical fibers may then be stretched, gathered or arranged, or lengthened or shortened based upon styles or designs of decorative objects to be applied in order
20 to construct appropriate shapes and patterns desired. The bundled end

of the optical fiber cords is secured to a device having a dynamic light-emitting mechanism comprising a light bulb, a color plate and a motor. When the light-emitting device is activated, light beams from the light bulb are passed through the transparent color plate, which rotates at a low speed and is also divided into regions of different colors and stripes. Next, the constantly changing and multicolor light beams produced are entered into the input ends of the optical fiber bundle, and are displayed as dynamic and exuberant colors via ends of the optical fibers to form multiple brilliant light spots distributed around the decorative objects.

However, in a prior optical fiber cord, due to characteristics of optical fibers, only one small light spot having a size equal to a sectional area of a certain optical fiber can be formed at an end of the optical fiber cord, and thus presentation of colors is somewhat limited. To attain large areas of light spots, it is necessary to substantially increase the quantity of the optical fibers. Not only production cost thereof is greatly increased, but also complications caused by arranging and securing large numbers of optical fibers are relatively elevated. Furthermore, shiny effects of conventional optical fiber cords are exhibited exclusively at ends of the cords in a form of light spots, and hence application flexibilities of glittering effects of the optical fibers are restrained. It shall be noted that designs

of decorative objects using optical fibers are frequently accommodated according to structural characteristics of optical fibers instead of being able to be freely and independently developed. As a result, some industrialists have tried to process middle portions of optical fiber cords by
5 either cutting or bending in order to change light-transmissive structures of the optical fibers, and light spots are indeed shown at the cut or bent portions. Yet, the optical fibers having been cut or bent are also damaged to a large extent with respect to the structures thereof. Therefore, the cut and bent optical fibers are often difficult to assemble or to use, and are
10 rather non-endurable by being easily fractured at the cut or bent portions.

SUMMARY OF THE INVENTION

In the view of the above, the object of the invention is to provide an optical fiber light-transmissive structure capable of overcoming the
15 aforesaid drawbacks namely limited light spots effects of prior optical fibers, and display instability (fractures and damages) apart from tips of prior optical fiber cords. The optical fiber light-transmissive structure in accordance with the invention has undamaged optical fiber structure strength, and also offers arrangement flexibilities of light-emitting
20 segments thereof, thereby enormously increasing a light-emitting area

therein as well as bringing splendid light effects.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 shows a structural schematic view illustrating a light-emitting
5 segment disposed at an end of an optical fiber cord according to the invention.

FIG. 2 shows a structural schematic view illustrating a light-emitting
segment disposed at a middle portion of an optical fiber cord according to
the invention.

10 FIG. 3 shows an embodiment according to the invention being applied
as an optical fiber bouquet.

FIG. 4 is an actual photograph showing splendid light-transmissive
effects in dark surroundings according to the invention.

15 DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

To better understand the structural characteristics and uses of the
invention, detailed descriptions shall be given with the accompanying
drawings hereunder.

Referring to FIGS. 1 and 2, according to the invention, an optical fiber
20 cord 10 is processed by rolling an appropriate position thereof, so as to

form a light-emitting segment 20 at the processed portion. First of all, without damaging the structure of the optical fiber cord 10 and yet retaining original strength thereof, sophisticated changes are caused at internal refracting planes of the light-emitting 20 after the rolling process.

5 Secondly, a refracting section of the light-emitting segment 20 displays an appropriate circular segment (a preferable length is between 10 to 15mm after repeated experiments) instead of a prototypic small area of the prior light spot. Consequently, the light-emitting area thereof is advanced to a gorgeous "light segment" from the conventional light spots, and
10 light-emitting effects are naturally much superior to those of the prior art.

Thirdly, the structure of the light-emitting segment 20 may be freely disposed at any position at the optical fiber cord 10 for that the structure of the light-emitting segment 20 is a non-destructive structure, thereby elevating application flexibilities of the invention.

15 Referring to FIG. 3, input ends 30 of a plurality of the optical fiber cords 10 according to the invention are bundled, and are secured to a dynamic light-emitting device 40. When the light-emitting device 40 is activated, multicolor and constantly changing light beams are entered into the input ends 30, and are then transmitted to the light-emitting segments
20 20 of individual optical fiber cords 10, thereby clearly displaying dashing

"light segments". The bright light effects produced and areas distributed by the "light segments" are far more outstanding than those of conventional optical fibers. Moreover, owing to flexibility characteristics of the light-emitting segments 20, the invention is especially suitable for decorative objects made of optical fibers and having dazzling and subtle designs for enhancing esthetical values and texture thereof. Referring to FIG. 4, particularly in dark surroundings, the bright light effects displayed as "light segments" are indeed magnificently brilliant, and are thus excellent for building an elegant atmosphere.

Conclusive from the above, in accordance with the invention, for that larger light-emitting areas are achieved while also maintaining structural strength of optical fiber cords, the lightness displayed by the optical fiber light-transmissive structure is distinct from that of the prior art, thereby more flexibly exhibiting splendid light effects by the light segments.

It is of course to be understood that the embodiment described herein is merely illustrative of the principles of the invention and that a wide variety of modifications thereto may be effected by persons skilled in the art without departing from the spirit and scope of the invention as set forth in the following claims.